US009636552B2

(12) **United States Patent**
Cleghorn et al.

(10) **Patent No.: US 9,636,552 B2**
(45) **Date of Patent: May 2, 2017**

(54) **GOLF CLUB HEAD WITH FLEXURE**

(71) Applicant: **Acushnet Company**, Fairhaven, MA (US)

(72) Inventors: **Richard L. Cleghorn**, Carlsbad, CA (US); **Darryl C. Galvan**, El Cajon, CA (US); **Stephanie Bezilla**, Carlsbad, CA (US); **Thomas Orrin Bennett**, Carlsbad, CA (US)

(73) Assignee: **Acushnet Company**, Fairhaven, MA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 190 days.

(21) Appl. No.: **14/588,137**

(22) Filed: **Dec. 31, 2014**

(65) **Prior Publication Data**

US 2015/0126304 A1 May 7, 2015

Related U.S. Application Data

(63) Continuation-in-part of application No. 14/584,822, filed on Dec. 29, 2014, which is a (Continued)

(51) **Int. Cl.**
A63B 53/04 (2015.01)
A63B 53/06 (2015.01)
(Continued)

(52) **U.S. Cl.**
CPC ***A63B 53/0466*** (2013.01); ***A63B 60/52*** (2015.10); ***A63B 60/54*** (2015.10); *A63B 2053/042* (2013.01); *A63B 2053/045* (2013.01); *A63B 2053/0408* (2013.01); *A63B 2053/0412* (2013.01); *A63B 2053/0433* (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC . A63B 60/54; A63B 60/52; A63B 2053/0458; A63B 2209/02; A63B 2053/0412; A63B 2053/042; A63B 2053/045; A63B 2053/0437; A63B 53/0466; A63B 2209/00;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

819,900 A 5/1906 Martin
1,705,997 A 3/1929 Quynn
(Continued)

FOREIGN PATENT DOCUMENTS

JP 1259876 10/1989
JP 2002-52099 2/2002
JP 2004-351054 12/2004

OTHER PUBLICATIONS

English language translation of JP Patent Publication No. 2002-52099A (full text).

Primary Examiner — Sebastiano Passaniti
(74) *Attorney, Agent, or Firm* — Michael J. Mancuso

(57) **ABSTRACT**

A golf club head including a crown, a sole, a hosel, a face, a flexure, and a weight member. The flexure provides compliance during an impact between the golf club head and a golf ball, and is tuned to vibrate, immediately after impact, at a predetermined frequency. The flexure is formed by a forward wall and a rearward wall that combine to form a recessed channel. The weight member is coupled to a weight mount that is at least partially disposed in the rearward wall of the flexure.

14 Claims, 33 Drawing Sheets